
MX95/105 Datasheet

By Amon Stinson, Don Vo and Simarbir Singh



The network performance benchmarks listed in the KB are target numbers based on initial testing and can change on further testing.

Overview

The Meraki **MX95/105** is an enterprise security appliance designed for distributed deployments that require remote administration across Medium branch environments. It is ideal for network administrators who demand both ease of deployment and a state-of-the-art feature set. The Meraki Dashboard allows for simple and easy deployment of the MX95/105 with minimal pre-configuration in almost any location.

Providing 4 x dedicated WAN uplinks, 2 x 10G SFP+ ports and 2 x RJ45 2.5G mGig ports. The LAN ports include 4 x RJ45 1GbE ports, and 2 x SFP+ 10G ports, the MX95/105 is ready for deployment in a variety of enterprise environments. MX95/105 appliance provides the following features:



Features

- Managed via Cisco Meraki Dashboard
- Automatic Firmware upgrades
- Meraki AutoVPN and L2TP/IPSec VPN endpoint
- Active Directory integration

- WAN Link Balancing
- Automatic WAN Failover
- SD-WAN over Meraki AutoVPN
- L3/L7 Stateful Firewall
- Geo based firewall rules
- 1:1 and 1:Many NAT
- Configurable VLANs / DHCP support
- Static Routing
- Client VPN endpoint
- Content Filtering
- Malware Protection (AMP) w/ optional Threat Grid integration
- IDS/IPS protection
- Custom Traffic Shaping
- Historical Client Usage statistics
- Netflow support
- Syslog integration
- Remote Packet Capture tools

Interfaces

- 2 x SFP+ / 10 Gigabit Ethernet ports dedicated for the WAN uplink
- 1 x RJ45 / 2.5 Gigabit Ethernet port dedicated for the WAN uplink
- 1 x RJ45 / 2.5 Gigabit Ethernet port with PoE+ capabilities dedicated for the WAN uplink
- 4 x RJ45 / 1 Gigabit Ethernet LAN ports
- 2 x SFP+ / 10 Gigabit Ethernet LAN ports
- 1 x RJ45 management port for local status page access
- 1 x USB 3.0 port

Context and Comparisons

	<u>MX85</u>	<u>MX95</u>	MX105
# of WAN Uplinks	4	4	4
Stateful Firewall Throughput	1 Gbps	2 Gbps	3 Gbps
Maximum VPN Throughput	500 Mbps	800 Mbps	1 Gbps
Advanced Security Throughput	750 Mbps	1Gbps	1.5 Gbps
PoE Capabilities	Yes, 1x RJ45 / 1 Gigabit Ethernet port (WAN)	Yes, 1x RJ45 / 1 Gigabit Ethernet port (WAN)	Yes, 1x RJ45 / 1 Gigabit Ethernet port (WAN)

Technical Breakdown

WAN Interface

MX85

2 x Dedicated 1 Gigabit Ethernet SFP
2 x Dedicated 1 Gigabit Ethernet RJ45

MX95/105

2x Dedicated 10 Gigabit Ethernet SFP+
2x Dedicated 2.5 Gigabit Ethernet RJ45



Note: The MX firmware currently supports a maximum of two Active WAN Uplinks. For more information about the interface behaviors, please refer to our [WAN behavior on MX75/85/95/105 documentation](#).

LAN Interface

MX85

8 x Dedicated 1 Gigabit Ethernet RJ45

2x Dedicated 1 Gigabit Ethernet SFP

MX95/105

4 x Dedicated 1 Gigabit Ethernet RJ45

2 x Dedicated 10 Gigabit Ethernet SFP+

Throughput and Capabilities

	<u>MX85</u>	<u>MX95</u>	<u>MX105</u>
Recommended Use Case	Small to medium branch with up to 250 users	Mid to large enterprise locations with 500 users	Mid to large enterprise locations with 750 users
Max site-to-site VPN Throughput	500 Mbps	800 Mbps	1 Gbps
Max Concurrent site-to-site VPN Tunnels	200	500	1000
Max Stateful Firewall Throughput	1 Gbps	2 Gbps	3 Gbps
Max Throughput with All Advanced Security features	750 Mbps	1Gbps	1.5 Gbps

Physical

	<u>MX85</u>	<u>MX-95</u>	<u>MX105</u>
Mount Type	Rack Mount	Rack Mount	Rack Mount
Dimensions	1.7" x 9.8" x 19"	1.73" x 11.23" x 19"	1.73" x 12.4" x 19"

(h x d x w)	43.8 x 250 x 484.6mm	44 x 285.2 x 484.6mm	44 x 315 x 484.6mm
Weight	8.2lb (3.7kg)	6.99lbs (3.17kg)	10.74lbs
			(4.87kg)
			2 Fans and 2 PSUs inserted
Input Operating Voltage	90-264VAC	100-127VAC,	100-127VAC,
	(47-63Hz)	200-240VAC (50/60Hz)	200-240VAC (50/60Hz)
PSU Model Number	N/A	N/A	Removable
			MA-PWR-150W AC
Power Load (idle/max)	12W / 55W	42W/ 109W	53W/ 123W
Operating Temperature	32°F to 104°F	32°F to 104°F	32°F to 104°F
	(0°C to 40°C)	(0°C to 40°C)	(0°C to 40°C)
Humidity	5% to 95%	5% to 95%	5% to 95%

Accessories

Accessory	Description
MA-PWR-CORD-US	1x AC Power Cable, US plug
MA-PWR-CORD-EU	1x AC Power Cable, EU plug
MA-PWR-CORD-UK	1x AC Power Cable, UK plug
MA-PWR-CORD-AU	1x AC Power Cable, AU plug
MA-RCKMNT-KIT-1	Optional: Rack mount screws kit. (Not included with MX95 and MX105)

Compatible Fiber Transceiver Modules

The Cisco Meraki MX95 and MX105 supports pluggable optics for high-speed backbone connections between wiring closets or to aggregation switches. Cisco Meraki offers several standards-based Gigabit and 10 Gigabit pluggable modules. Each appliance has also been tested for compatibility with several third party modules.

Product ID	Fiber Type
MA-SFP-1GB-SX	Multi-Mode Fiber (MMF)
MA-SFP-1GB-LX10	Single-Mode Fiber (SMF)

MA-SFP-1GB-TX	N/A (RJ45 Copper SFP)
MA-SFP-10GB-SR	Multi-Mode Fiber (MMF)
MA-SFP-10GB-LR	Single-Mode Fiber (SMF)
MA-SFP-10GB-LRM	Single-Mode Fiber (SMF)
MA-SFP-10GB-LRM	Multi-Mode Fiber (MMF)
MA-SFP-10GB-ER2	Single-Mode Fiber (SMF)
MA-SFP-10GB-ZR	Single-Mode Fiber (SMF)

Direct Attach

Product ID	Description
MA-CBL-TA-1M	10GSFP+Cu, 1m Passive Twinax
MA-CBL-TA-3M	10GSFP+Cu, 3m Passive Twinax



Note: Please refer to the [Meraki SFP Datasheet](#) for additional information about the SFP Accessories

Troubleshooting

Common Event Log Messages

There are currently no MX95/105 specific event log entries, for more general information about navigating the event log and the types of events that could be expected, please check out our [Event Log documentation](#).