

Switch Enterprise 8 PoE



Mechanical

Dimensions	200 x 248 x 44 mm (7.9 x 9.8 x 1.7")
Weight	2.4 kg (5.29 lb)
Enclosure material	Polycarbonate
Mount material	Polycarbonate

Hardware

Total non-blocking throughput	40 Gbps
Switching capacity	80 Gbps
Forwarding rate	59.52 Mpps
Max PoE power	120W
Power method	(1) 100–240V AC, 2A Max., 50/60 Hz, Universal Input
Power supply	AC/DC, Internal, 150W
Management interface	Ethernet In-Band
Networking interface	(8) 1/2.5 GbE RJ45
SFP+ interface	(2) 1/10 Gbps SFP+
PoE interface	(8) PoE/PoE+ (Pins 1, 2+; 3, 6-)
Max. PoE+ wattage per port by PSE	32W
Voltage range PoE mode	44–57V
Voltage range PoE+ mode	50–57V
LCM display	(1) 1.3" Touchscreen Bootup animation: Bootup in progress Firmware upgrade icon: Firmware upgrading Steady White: Factory Defaults, Awaiting Adoption Steady Blue: Device is Adopted
ESD/EMP protection	Air: ± 16 kV Contact: ± 12 kV
Operating temperature	-5 to 45° C (23 to 113° F)
Operating humidity	10 to 90% noncondensing
Certifications	CE, FCC, IC

LEDs

Ethernet	White: Link or activity
SFP+	White: Link or activity



Specifications are subject to change. Ubiquiti products are sold with a limited warranty described at www.ui.com/support/warranty

©2021 Ubiquiti Inc. All rights reserved. Ubiquiti, Ubiquiti Networks, the Ubiquiti U logo, the Ubiquiti beam logo, UniFi, and UniFi Network are trademarks or registered trademarks of Ubiquiti Inc. in the United States and in other countries. All other trademarks are the property of their respective owners.